


1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
3. Product code: M032-C101, C121

ITEM	Hoshizaki Cube Ice Maker	
MODEL	IM-130A	
AC SUPPLY VOLTAGE	1 PHASE 220-240V 50Hz	
AMPERAGE	2.7A (AT.32°C, WT.21°C)	
STARTING AMPERAGE	25A	
ELECTRIC CONSUMPTION	630W (AT.32°C, WT.21°C)	
POWER FACTOR	97%	
POWER SUPPLY CAPACITY	Min. 1.64kVA (6.9A)	
ICE PRODUCTION PER 24h	Approx. 120kg (5mm) / 126kg (15mm)(AT.10°C, WT.10°C)	
	Approx. 116kg (5mm) / 125kg (15mm)(AT.21°C, WT.15°C)	
	Approx. 90kg (5mm) / 100kg (15mm)(AT.32°C, WT.21°C)	
WATER CONSUMPTION PER 24h	Approx. 0.50m ³ (5mm) (AT.10°C, WT.10°C)	
	Approx. 0.25m ³ (5mm) (AT.21°C, WT.15°C)	
	Approx. 0.19m ³ (5mm) (AT.32°C, WT.21°C)	
SHAPE OF ICE	Cube Approx. 28×28×32mm	
FREEZE CYCLE TIME	23min (5mm) (AT.21°C, WT.15°C)	
ICE PRODUCTION PER CYCLE	1.8kg/80pcs.(5mm)(AT.21°C, WT.15°C)	
MAX STORAGE CAPACITY	52kg(Bin Control Setting Approx. 34kg)	
DIMENSIONS	660mm(W) × 570mm(D) × 1200mm(H)	
EXTERIOR	Stainless Steel, Plastic Door & Louver, Galvanized Steel(Rear)	
INSULATION	Polyurethane Foam	
INSULATION FOAM BLOWING AGENT	Cyclopentane / CFC Free / ODP: 0 / GWP: 3	
CONNECTIONS-ELECTRIC	X-Type Connection	
CONNECTIONS-WATER SUPPLY	Inlet G1/2" (connected at rear side)	
CONNECTIONS-DRAIN	Outlet I.D. φ22mm (connected at rear side)	
ICE MAKING SYSTEM	Cell type	
HARVESTING SYSTEM	Hot Gas Defrost	
COMPRESSOR	Hermetic	
CONDENSER	Air-cooled	
HEAT REJECTION	1410W 1213kcal/h	
EVAPORATOR	Tin-plated Copper Tube on Sheet and Cells	
REFRIGERANT CONTROL	Thermostatic Expansion Valve	
REFRIGERANT CHARGE	R404A / 350g	
ICE MAKING CONTROL SYSTEM	Thermistor, Timer	Controller Board
HARVESTING CONTROL SYSTEM	Thermistor	
BIN CONTROL SYSTEM	Microswitch with Time Delay	
ICE MAKING WATER CONTROL SYSTEM	Timer, Water Pan's movement	
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse	
COMPRESSOR PROTECTION	Auto-reset Overload Protector	
ICE MAKER PROTECTION	Interlock by Controller Board	
WEIGHT	Net weight 79kg/Gross weight 98kg	
PACKAGE	Carton 760mm(W) × 680mm(D) × 1389mm(H)	
ACCESSORIES	Scoop, Leg, Installation Kit	
OPERATING CONDITIONS	Ambient Temp.:1-40°C,Water Supply Temp.:5-35°C	
	Water Supply Pressure:0.07-0.78MPa(0.7-8bar) Voltage Range: Rated Voltage±6%	

※ We reserve the right to make changes in specifications and design without prior notice.

HOSHIZAKI CUBE ICE MAKER IM-130A

APPROVED KUROYANAGI	CHECKED MORIMOTO	DESIGNED KONDO	DRAWN WATANABE	SCALE 1/10	TRIGONOMETRY
KUROYANAGI APPROVED	KONDO DESIGNED	2014.02.11 DATE	2013.07.24 DATE	DRAWING NO. D13260	SYMBOL 2



1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
3. Product code: M032-C105

ITEM	Hoshizaki Cube Ice Maker		
MODEL	IM-130A-23		
AC SUPPLY VOLTAGE	1-PHASE 220-240V 50Hz		
AMPERAGE	2.7A (AT.32°C, WT.21°C)		
STARTING AMPERAGE	25A		
ELECTRIC CONSUMPTION	630W (AT.32°C, WT.21°C)		
POWER FACTOR	97%		
POWER SUPPLY CAPACITY	Min. 1.64kVA (6.9A)		
ICE PRODUCTION PER 24h	Approx. 100kg (5mm) / 106kg (15mm)(AT.10°C, WT.10°C)		
	Approx. 96kg (5mm) / 102kg (15mm)(AT.21°C, WT.15°C)		
	Approx. 80kg (5mm) / 88kg (15mm)(AT32°C, WT.21°C)		
WATER CONSUMPTION PER 24h	Approx. 0.53m ³ (5mm) (AT.10°C, WT.10°C)		
	Approx. 0.28m ³ (5mm) (AT.21°C, WT.15°C)		
	Approx. 0.22m ³ (5mm) (AT32°C, WT.21°C)		
SHAPE OF ICE	Cube Approx. 28×28×23mm		
FREEZE CYCLE TIME	23min (5mm) (AT.21°C, WT.15°C)		
ICE PRODUCTION PER CYCLE	1.3kg/80pcs.(5mm)(AT.21°C, WT.15°C)		
MAX STORAGE CAPACITY	52kg(Bin Control Setting Approx. 34kg)		
DIMENSIONS	660mm(W) x 570mm(D) x 1200mm(H)		
EXTERIOR	Stainless Steel, Plastic Door & Louver, Galvanized Steel(Rear)		
INSULATION	Polyurethane Foam		
INSULATION FOAM BLOWING AGENT	Cyclopentane / CFC Free / ODP: 0 / GWP: 3		
CONNECTIONS-ELECTRIC	X-Type Connection		
CONNECTIONS-WATER SUPPLY	Inlet G1/2" (connected at rear side)		
CONNECTIONS-DRAIN	Outlet I.D. φ22mm (connected at rear side)		
ICE MAKING SYSTEM	Cell type		
HARVESTING SYSTEM	Hot Gas Defrost		
COMPRESSOR	Hermetic		
CONDENSER	Air-cooled		
HEAT REJECTION	1410W 1213kcal/h		
EVAPORATOR	Tin-plated Copper Tube on Sheet and Cells		
REFRIGERANT CONTROL	Thermostatic Expansion Valve		
REFRIGERANT CHARGE	R404A / 350g		
ICE MAKING CONTROL SYSTEM	Thermistor, Timer		Controller Board
HARVESTING CONTROL SYSTEM	Thermistor		
BIN CONTROL SYSTEM	Microswitch with Time Delay		
ICE MAKING WATER CONTROL SYSTEM	Timer, Water Pan's movement		
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse		
COMPRESSOR PROTECTION	Auto-reset Overload Protector		
ICE MAKER PROTECTION	Interlock by Controller Board		
WEIGHT	Net weight 79kg/Gross weight 98kg		
PACKAGE	Carton 760mm(W) x 680mm(D) x 1389mm(H)		
ACCESSORIES	Scoop, Leg, Installation Kit		
OPERATING CONDITIONS	Ambient Temp.:1-40°C,Water Supply Temp.:5-35°C		
	Water Supply Pressure:0.07-0.78MPa(0.7-8bar) Voltage Range: Rated Voltage±6%		

■ We reserve the right to make changes in specifications and design without prior notice.

HOSHIZAKI CUBE ICE MAKER IM-130A-23

APPROVED KUROYANAGI	CHECKED MORIMOTO	DESIGNED KONDO	DRAWN WATANABE	SCALE 1/10	TRIGONOMETRY
* APPROVED	* DESIGNED	△ SYMBOL	***** DATE	DATE 2014.03.24	DRAWING NO. D14210